IN THE CLAIMS

- 1 5. (Cancelled)
- 6. (Currently Amended) The multi-layer laminate of claim 5 A formable thermoplastic multi-layer laminate comprising

an outer layer comprising a polymer comprising resorcinol arylate polyester chain members,

a middle layer comprising a thermoplastic polymer, and

an inner-tie layer comprising a thermoplastic polymer comprising a carbonate polymer and an acrylonitrile-styrene graft copolymer comprising an acrylonitrile-styrene-acrylate graft copolymer (ASA) and wherein the acrylonitrile-styrene-acrylate graft copolymer (ASA) further comprises_a styrene acrylonitrile copolymer (SAN),

the middle layer being between the outer layer and the inner-tie layer and being in contact with both the outer layer and the inner-tie layer.

- 7. (Cancelled)
- 8. (Currently Amended) The multi-layer laminate of claim 1 claim 6, wherein the inner-tie layer comprises about 25 to about 80 wt.% polycarbonate based on the total weight of the inner-tie layer.
- 9. (Currently Amended) The <u>multilayer laminate of Claim 6, formed article of claim</u> 3-wherein the inner-tie layer comprises a thermoplastic polymer comprising from about 25 to about 80 weight % of carbonate polymer, from about 10 to about 35 weight % of the acrylonitrile-styrene graft copolymer and from about 10 to about 40 weight % of the styrene copolymer, the weight % being based on the total weight of the inner-tie layer.

- 10. (Original) The multi-layer laminate of claim 9 wherein the inner-tie layer comprises a thermoplastic polymer comprising from about 40 to about 80 weight % carbonate polymer, from about 10 to about 30 weight % of the acrylonitrile-styrene graft copolymer and from about 10 to 30 weight % of the styrene copolymer, based on the total weight of the inner-tie layer.
- 11. (Currently Amended) The multi-layer laminate of claim 1- A formable thermoplastic multi-layer laminate comprising

an outer layer comprising a polymer comprising resorcinol arylate polyester chain members,

a middle layer comprising a thermoplastic polymer, and

an inner-tie layer comprising a thermoplastic polymer comprising a carbonate polymer, wherein the inner-tie layer further comprises a stabilizer comprising an alkylthioester, and an acrylonitrile-styrene graft copolymer comprising at least one of an acrylonitrile-styrene-acrylate graft copolymer (ASA) or an acrylonitrile-butadiene-styrene graft copolymer (ABS),

the middle layer being between the outer layer and the inner-tie layer and being in contact with both the outer layer and the inner-tie layer.

- 12. (Previously Presented) The multi-layer laminate of claim 11 wherein the inner-tie layer further comprises a stabilizer comprising pentaerythritol tetrakis(beta-laurylthiopropionate).
 - 13. (Cancelled)
- 14. (Currently Amended) The multi-layer laminate of elaim 1 claim 11 wherein the inner-tie layer comprises a thermoplastic polymer having a melt flow index of from about 3 to about 30 cm³/10min (at 260°C/5kg).
- 15. (Currently Amended) The multi-layer laminate of elaim 1 claim 11 wherein the outer layer has an outermost surface comprised of at least one sub-layer comprising resorcinol arylate polyester chain members.

- 16. (Original) The multi-layer laminate of Claim 15, wherein the at least one sublayer comprises an iso-terephthalic resorcinol/bis-phenol-A copolymer.
- 17. (Original) The multi-layer laminate of claim 15 wherein the outer layer further comprises at least one additional sublayer.
- 18. (Original) The multi-layer laminate of claim 17 wherein the outer layer consists of at least three additional sub-layers.
 - 19 22. (Cancelled)
- 23. (Currently Amended) The multi-layer laminate of-claim 1 claim 11 wherein the outer layer has a thickness about 3 to about 30 mils.
 - 24-26. (Cancelled)
- 27. (Currently Amended) The formed multi-layer laminate of claim 25 A formed multi-layer laminate comprising the multi-layer laminate of claim 6 wherein the formed multi-layer laminate is formed by vacuum forming.
 - 28. (Cancelled)

29. (Currently Amended) An article comprising

a formable thermoplastic multi-layer laminate comprising

an outer layer comprising a polymer comprising resorcinol arylate polyester chain members,

a middle layer comprising a thermoplastic polymer,

an inner-tie layer comprising a thermoplastic polymer comprising a carbonate polymer and an acrylonitrile-styrene graft copolymer comprising at least one of an acrylonitrile-styrene-acrylate graft copolymer (ASA) or an acrylonitrile-butadiene-styrene graft copolymer (ABS),

the middle layer being juxtaposed between the outer layer and the inner-tie layer and being in continuous contact with both the outer layer and the inner-tie layer, and

a substrate bonded to the inner-tie layer, The formed article of claim 28-wherein the substrate comprises is at least one of a thermosetting material, a thermoplastic material, a foamed material, a plastic, a reinforced thermoplastic material, and combinations thereof.

30. (Cancelled)

31. (Currently Amended) An article comprising

a formable thermoplastic multi-layer laminate comprising

an outer layer comprising a polymer comprising resorcinol arylate polyester chain members,

a middle layer comprising a thermoplastic polymer,

an inner-tie layer comprising a thermoplastic polymer comprising a carbonate polymer and an acrylonitrile-styrene graft copolymer comprising at least one of an acrylonitrile-styrene-acrylate graft copolymer (ASA) or an acrylonitrile-butadiene-styrene graft copolymer (ABS),

the middle layer being juxtaposed between the outer layer and the inner-tie layer and being in continuous contact with both the outer layer and the inner-tie layer, and

<u>a substrate bonded to the inner-tie layer, The article of claim 29-wherein the foamed</u> <u>material_substrate_comprises a foamed polyurethane material.</u>

32 - 38. (Cancelled)

39. (Currently Amended) The article of claim 28 claim 29 comprising an exterior surface having a class "A" finish.

40-46. (Cancelled)